



Cat.6 S/FTP Cable, Yellow, 20m

No.: 47770

Patch Cable

Description

- Assembled S/FTP Patch Cable
- PIMF cable (pairs in metal foil)
- 10/100 / 1000Base-TX support
- Category 6, Class E, 27 AWG, 4 pairs
- Gigabit compatible
- **Connector:** RJ45 shielded, Snagless (jack Protection), gold-plated contacts
- Corresponds to: ANSI / TIA-568-C.2
- Used according to colour code: TIA / EIA-568-B
- Colour: Yellow
- 10 year warranty

The Lindy CAT6 RJ45 S/FTP patch leads are manufactured and tested to conform to ISO 11801 specification. The unique snagless strain relief design prevents damage to the connector latch during installation and removal. Every cable is 100% performance tested and comes with the Lindy "no surprises" guarantee.

These cables are ideal for connecting computers, hubs, switches, print servers and patch panels as well as finding more and more uses in AV applications and security camera systems.

Technical details

Connectors

- Connector A: RJ45 Male
- Connector B: RJ45 Male
- Housing Material: Polycarbonate
- Connector Plating: Nickel
- Pin Construction: Copper Alloy
- Pin Plating: Gold plated
- Dimensions (approx.) WxDxH: 11.6x22.8x8.3mm (0.46x0.90x0.33in)

Cable Construction

- Length: 20m (65.62ft)
- Colour: Yellow
- Type: Cat.6
- Jacket Diameter: 6.2mm (0.24in)

- Jacket Material: PVC
- Conductor Material: Copper
- Conductor Gauge: 27AWG
- Shielding: Aluminium Braid

Specifications

- Supported Bandwidth: 250MHz
- Nominal Attenuation: 32.8dB/100m @250MHz
- Minimum Bend Radius: 74mm (2.91in)
- Operating Temperature: -10°C - 60°C (14°F - 140°F)
- Storage Temperature: -20°C - 75°C (-4°F - 167°F)

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 10
- Certificated: RoHS, REACH, UL, California Proposition 65

Purchasing Information

- No.: 47770
- EAN: 4002888477703

This product is also available in other lengths:

- 47760 - 0.3m (0.98ft)
- 47761 - 0.5m (1.64ft)
- 47762 - 1m (3.28ft)
- 47763 - 1.5m (4.92ft)
- 47764 - 2m (6.56ft)
- 47765 - 3m (9.84ft)
- 47766 - 5m (16.44ft)
- 47767 - 7.5m (24.61ft)
- 47768 - 10m (32.81ft)
- 47769 - 15m (49.21ft)
- 47770 - 20m (65.62ft)
- 47771 - 30m (98.43ft)