



ERK SERIES RACK, 27 RU, 25"D

ERK-2725 |

FEATURES & BENEFITS

An economical standalone rack with solid sides, the ERK series can also be ganged to create partitioned multi-bay installations for thermal management control, future growth or other purposes. Seismic certified to protect your components.



- Fully welded construction for strength
- Enclosure sides include top and bottom venting
- Convenient lacing points and slotted rail brackets for cable management
- Standard front adjustable 10-32 threaded rackrail with numbered spaces
- Includes standard configurable rear door

SPECIFICATIONS

GENERAL INFO

Finish: Textured Black Powder Coat
UL Standards Tested: UL2416

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

ASCE: 7-10
RoHS: Yes
Greenguard: Yes
UL Listing No: E173107

DIMENSIONS

Usable Depth: 23.47
Usable Height: 47.375
Panel Width: 19

Capacity Weight (US): 10000
Depth (US): 25
Height (US): 51.375
Width (US): 22
Rack Units: 27

TECHNICAL INFORMATION

Rackrail Type: 10-32
Seismic Load Capacity: 600
Static Load Capacity: 10000
UL Load Capacity: 2500
Material: Steel
Mounting: Horizontal
Seismic Rating: Yes