



1.5m USB 3.1 Type C Cable 3A, Black Line

No.: 36907

USB Type C Male to C Male

Description

- Entry level USB 3.1 Type C to C 3A (60W) cable for home and small office applications
- Supports SuperSpeed+ data transfer speeds up to 10Gbps
- Robust PVC housing, nickel connectors, gold plated contacts
- Triple shielded cable, corrosion resistant tinned copper conductors
- SuperSpeed+, USB 3.1, 10Gbps; 10 year warranty

From the lines cable connectivity concept developed by Lindy, Black Line USB 3.1 Type C to C cables are fully featured, entry level high resolution connection solutions, perfect for home and small office use.

USB Type C features a reversible connector, so no matter which orientation the cable is inserted, a connection will always be found. This connector allows a fully bi-directional cable with automatic host and device negotiation.

Black Line USB 3.1 Type C to C cables feature triple shielded construction with tinned copper conductors for premium performance and corrosion resistance. Nickel connectors and gold plated contacts maintain signal integrity and reliability.

The SuperSpeed+ protocol is supported with up to 10Gbps bandwidth for rapid transfer of large data volumes.

Black Line USB 3.1 Type C to C cables are available in lengths from 0.5m, 1m and 1.5m

Technical details

Connectors

- Connector A: USB 3.1 Type C Male
- Connector B: USB 3.1 Type C Male
- Housing Material: PVC
- Connector Plating: Nickel
- Pin Construction: Phosphor Bronze
- Pin Plating: 24K Gold plated
- Dimensions (approx.) WxDxH: 11.0x25.5x7.3mm (0.43x1.00x0.29in)

Cable Construction

- Length: 1.5m (4.92ft)
- Standard: USB 3.1
- Colour: Black
- Type: Round

- Jacket Diameter: 4.5mm (0.18in)
- Jacket Material: PVC
- Conductor Material: Tinned Copper
- Conductor Gauge: 26/32/32AWG
- Shielding: Tinned Copper Braid 75%

Specifications

- Supported Bandwidth: 10Gbps
- Maximum Resolution: -
- Nominal Attenuation: 0.5Mhz – 15Ghz < 40db
- Minimum Bend Radius: 45mm (1.77in)
- Operating Temperature: -20°C - 80°C [-4°F - 176°F]
- Storage Temperature: -25°C - 85°C [-13°F - 185°F]
- ATC Approved: -

Miscellaneous

- Packaging Type: Polybag
- Warranty [Years]: 10
- Certificated: RoHS, REACH, UL

Purchasing Information

- No. 36907
- EAN: 4002888369077

This product is also available in other lengths

- 36905 - 0.5m (1.64ft)
- 36906 - 1m (3.28ft)
- 36907 - 1.5m (4.92ft)