

# Speaker Cable Meridian Install SP215; 2 x 1,50 mm<sup>2</sup>; FRNC, shielded Ø 8,00 mm; grey

## Art. No.: 415-0056FG

**ANALOG** **FRNC** **HALOGEN-FREE** **OFC**



### General Data

Article number :	415-0056FG
Name :	Meridian Install SP215
EAN :	4049371005258
Properties :	Analog
Properties :	Halogen-free / LSZH
Properties :	FRNC flame retardant
Properties :	OFC oxygen free copper
Application area :	Studio / Broadcast
Application area :	Installation
Application area :	ELA 100 V
Application :	Speaker Cable
Application :	Installation cable
Colour :	grey
BPVo-Euroclass :	Fca

### Technical Data

Construction :	(2LIY1,50mm <sup>2</sup> )(ST)CY
Construction (audio) :	(2LIY1,50mm <sup>2</sup> )Y
Jacket material :	FRNC, shielded
Jacket Ø [mm] :	8,00
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm <sup>2</sup> ] :	1,50
Inner conductor Ø (audio) [mm] :	1,38
AWG (audio) :	16
Copper strands (audio) :	84
Copper strand Ø (audio) [mm] :	0,15
Conductor insulation Ø [mm] :	2,62
Weight per 1 m [g] :	78
Fire load per m [kWh] :	0,29
Style variant :	round
Packing :	100 m spool
Packing :	500 m spool
Temperature min. [°C] :	-30
Temperature max. [°C] :	70
Width [mm] :	8
Height [mm] :	8

### Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	150
Insulation resist. per 1 km [GΩ] :	0,005
Insulation resist. per 1 km (audio) [GΩ] :	0,005
Conductor resistance per 1 km [Ω] :	13