

DATASHEET

RJ45 Hirose Connector Set STP, TM21 Cat.6 black





Description

Channel Class E up to 250 MHz (Cat.6)
 For stranded wires (AWG 24/7, AWG 26/7, AWG 27/7)
 Shielded version
 Core insulation about 0.9 - 1.0 mm
 Cable diameter max. 6.6 mm
 The set consists of RJ plug, anti-kink sleeve and guide plate
 Suitable crimping tool DCW1002 + DCW1002.1 or 39934.2

General data

Category	6
Model	jack (jack)
Connection type	crimp
Type of connector	RJ45 8(8)
Screened	True
AWG-range for litz wire conductor	24 - 27
AWG-range for solid core	24 - 26
Special tool necessary	True
Suitable for round cable	True
Suitable for flat cable	False
Suitable for litz wire conductor	True
Suitable for solid core	False

Available variants

Article no.	Title	Colour
H7641.4-1	RJ45-Hirose Connector TM21 black, 1 pcs., 3 Elements, Cat.6	black
H7641.4-50	RJ45-Hirose Connector TM21 black 50 pcs., 3 Elements, Cat. 6	black

This datasheet was created automatically on 18-11-2020 . Technical changes reserved.



DATASHEET



RJ45 Hirose Connector Set STP, TM21 Cat.6 black

H7641.4-100

RJ45-Hirose Connector TM21 black 100 pcs., 3 Elements, Cat.6

black

This datasheet was created automatically on 18-11-2020 . Technical changes reserved.



EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

