



## SRSR SERIES RACK, SRSR-4-30

SRSR-4-30 |

### FEATURES & BENEFITS

Specify an SRSR for easy rear access to equipment connections in millwork, cabinets and flush in-wall installations. Available with a 19" or 23" useable depth, the SRSR system extends and rotates 90° in either direction, making it ideal for smaller systems.



- Removable rack frame allows in-shop integration and on-site installation of equipment
- Locks in the extended position for simplified equipment integration
- Rotating equipment bay locks in place at 0°, 60° and 90° for easy installation and servicing
- Self-centering mounting base makes it simple to align system within cabinet opening
- Rear cable support works in conjunction with rear rackrail for effective cable management
- Standard front and rear 10-32 threaded rackrail with marked spaces

### SPECIFICATIONS

#### GENERAL INFO

Finish: Flat Black Powder Coat

#### LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

RoHS: Yes

Greenguard: Yes

#### DIMENSIONS

Usable Depth: 17.25" (2" Setback) – 19.00" (1/4" Setback)

Usable Height: 52.5

Capacity Weight (US): 250

Depth (US): 19.14

Height (US): 55.5

Width (US): 19.125

Rack Units: 30

## TECHNICAL INFORMATION

Rackrail Type: 10-32  
Static Load Capacity: 250  
Material: Steel  
Mounting: Horizontal