

Installation cable Meridian Install SP240 CPR- Version; 2 x 4,00 mm²; FRNC Ø 10,20 mm; black; Cca

Art. No.: 440-0051FC

ANALOG FRNC HALOGEN-FREE OFC



General Data

Article number :	440-0051FC
Name :	Meridian Install SP240 CPR- Version
EAN :	4049371385237
Properties :	OFC oxygen free copper
Properties :	FRNC flame retardant
Properties :	Halogen-free / LSZH
Properties :	Analog
Application area :	ELA 100 V
Application area :	Installation
Application area :	Studio / Broadcast
Application :	Installation cable
Application :	Speaker Cable
Colour :	black
BPVo-Euroclass :	Cca

Conductor resistance per 1 km [Ω] : 4,5

Technical Data

Construction :	(2LIY4,0mm ²)Y
Jacket material :	FRNC
Jacket Ø [mm] :	10,20
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm ²] :	4,00
Inner conductor Ø (audio) [mm] :	2,26
AWG (audio) :	11
Copper strands (audio) :	56
Copper strand Ø (audio) [mm] :	0,30
Conductor insulation Ø [mm] :	4,20
Weight per 1 m [g] :	150
UV-resistant :	yes
Fire load per m [kWh] :	0,54
Style variant :	round
Packing :	500 m spool
Packing :	100 m spool
Temperature min. [°C] :	-30
Temperature max. [°C] :	70
Width [mm] :	10,2
Height [mm] :	10,2

Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	125
Insulation resist. per 1 km [GΩ] :	0,005
Insulation resist. per 1 km (audio) [GΩ] :	0,005