



## NADB15MF

15 pole D-SUB feedthrough, male to female

### Features & Benefits

- Ideal for audio networking and integration of equipment into video systems

## Technical Information

| Product       |          |
|---------------|----------|
| <b>Title</b>  | NADB15MF |
| <b>Gender</b> | male     |

| Electrical                           |            |
|--------------------------------------|------------|
| <b>Contact resistance</b>            | 30 mΩ      |
| <b>Insulation resistance</b>         | > 5 GΩ     |
| <b>Number of electrical contacts</b> | 15         |
| <b>Rated current per contact</b>     | 3 A        |
| <b>Rated voltage</b>                 | 50 V ac    |
| <b>Dielectric strength</b>           | > 0.5 kVac |

| Mechanical                |                |
|---------------------------|----------------|
| <b>Panel thickness</b>    | 4 mm           |
| <b>Wiresize</b>           |                |
| <b>Wiring</b>             | Feedthrough    |
| <b>Mounting direction</b> | Front mounting |
| <b>Chassis shape</b>      | D              |

| Material        |                         |
|-----------------|-------------------------|
| Contact plating | Au                      |
| Contacts        | Brass (CuZn39Pb3)       |
| Insert          | Steel , tin plated, PBT |
| Shell           | Zinc diecast (ZnAl4Cu1) |
| Shell plating   | Nickel                  |

| Environmental     |                  |
|-------------------|------------------|
| Flammability      | UL 94-V0         |
| Temperature range | -25 °C to +85 °C |