

DATASHEET

19" 1U Socket Strip with Full Device Protection



Description

Mains- and frequency filter
 Overvoltage protection leakage current 6.5 kA
 Visual function and failure display
 35° turned socket inserts in the aluminium profile
 Cable H05VV-F 3G 1.5 mm², black, 2.0 m, 250 V AC / 16 A with angled CEE7/3 plug CEE7/7
 Supplied mounting brackets allow any fastening position

General data

Material	metal
Material quality	Thermoplastic
Housing shape	Rectangular
Mains filter	True
Over voltage protection	True
Nominal current	16 A
Core cross section	1.50 mm ²
With cover	False
Halogen free	False
Surface treatment	anodising
Type of surface	Not applicable
Degree of protection (IP)	IP20

This datasheet was created automatically on 09-12-2020 . Technical changes reserved.



DATASHEET

19" 1U Socket Strip with Full Device Protection

General data

Rotated central insert	True
Angle rotated central insert	35°
Residual current circuit breaker (RCCB)	False
Transparent	False
Length of power cord	2.0 m

Available variants

Article no.	Title	On/Off switch	Number of socket outlets with protective contact	Colour	RAL-number (akin)
691689	19" 1U Socket Strip 6 x CEE7/3 with Surge Protection + Mains Filter, grey	False	6	grey	7035
691689SW	19" 1U Socket Strip 6 x CEE7/3 with Surge Protection + Mains Filter, black	False	6	black	

This datasheet was created automatically on 09-12-2020 . Technical changes reserved.

