

Mini DisplayPort to HDMI Video Adapter Converter - White

Product ID: MDP2HDW



The MDP2HDW passive Mini DisplayPort to HDMI Video Adapter/Converter (White) offers a convenient HDMI/Mini-DisplayPort link, which enables you to connect an HDMI computer monitor or television to a device with a Mini-DisplayPort output (such as any Microsoft Surface Pro with mDP), while saving the expense of upgrading the monitor for compatibility.

The adapter supports high resolution output up to 1920x1200, offering a high quality solution for mirroring or extending a computer desktop onto a second display.

This versatile Mini DisplayPort to HDMI adapter requires a multimode DisplayPort port (DisplayPort ++) connection to function, and is compatible with Intel Thunderbolt output when connected directly to a supporting DisplayPort over Thunderbolt I/O port.

This adapter allows for audio pass-through if supported by the video source. Please review the video source manual to confirm support.

Backed by a StarTech.com 3-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Ideal for digital entertainment centers, home offices, business conference rooms and trade show displays
- Keep your existing HDMI monitor to be used with your new Mini-DisplayPort device
- Ideal for using your HDMI monitor as a secondary display



Features

- Easy to use passive cable, no software required
- Supports PC resolutions up to 1920x1200 and HDTV resolutions up to 1080p

• Compatible with Intel Thunderbolt

Hardware

Warranty 3 Years

Active or Passive Adapter Passive

AV Input Mini DisplayPort - 1.2

AV Output HDMI - 1.4

Audio Yes

DisplayPort 1.1a **Industry Standards**

HDMI 1.3a

Chipset ID NXP - PTN3361

Performance

Maximum Cable Distance 49.9 ft [15.2 m]

To Display

Maximum Digital Resolutions

1920x1200 / 1080p

Audio Specifications HDMI - 7.1 Channel Audio

MTBF MDP2HDW hours

Connector(s)

Connector A Mini-DisplayPort (20 pin)

Connector B HDMI (19 pin)

Special Notes / Requirements

> System and Cable DP++ port (DisplayPort ++) required on video card or video source

Requirements (DVI and HDMI pass-through must be supported)

Environmental

Operating Temperature 0C to 60C (32F to 140F)



Storage Temperature -10C to 7	10C (14	4⊦ to '	158F)
-------------------------------	---------	---------	-------

Humidity 40~85% RH

Physical
Characteristics

Color White

Cable Length 4.7 in [12 cm]

Product Length 6.7 in [17 cm]

Product Width 1.6 in [40 mm]

Product Height 0.6 in [15 mm]

Weight of Product 0.8 oz [24 g]

Packaging Information

Package Length 9.4 in [24 cm]

Package Width 6.3 in [16 cm]

Package Height 0.8 in [20 mm]

Shipping (Package)

Weight

1.8 oz [50 g]

What's in the Box

Included in Package Mini-DisplayPort to HDMI converter

^{*}Product appearance and specifications are subject to change without notice.