

DATASHEET

Duplex Jumper LC-LC, 50/125 μ , OM2, steel armored



Description

SOLID!

Crush-resistance = 30.000 N per square centimeter
equals 3 tons / cm²

Stainless steel spiral coil and stainless steel braid for high mechanical protection

Non-crushable, shock-proof, bend-resistant

Very high flexibility

High lateral pressure and tensile resistance

General data

Fibre type	Multimode 50/125
Category	OM2
Number of fibres	2
Anti-kink sleeve	put-on
Type of connector connection 1	LC-Duplex
Connector colour 1	beige
Type of connector connection 2	LC-Duplex
Connector colour 2	beige

Cable construction

Cable type	Duplex
Cable Construction	Duplex

This datasheet was created automatically on 18-11-2020 . Technical changes reserved.



DATASHEET

Duplex Jumper LC-LC, 50/125 μ , OM2, steel armored

Cable construction

Cable \emptyset	3.0 mm
-------------------	--------

Cable sheath

Colour outer sheath	grey
Jacket Material	LSZH
Flame retardant	According to EN 50265-2-1

Environmental conditions

Operating Temperature	-20 – 75 °C
Storage Temperature	-20 – 85 °C

Transmission characteristics

Quality class multimode	A/1 nach IEC-61753-222-2
-------------------------	--------------------------

Standards, approvals, certifications

Cabling standard	ISO/IEC 11801;EN-50173-1
Cable Conform to Standard	IEC 60793-2

Available variants

Article no.	Title	Length
O6504.1	Duplex Jumper LC-LC 50/125 μ , OM2, LSZH, armored, grey, 3.0mm, 1m	1.0 m
O6504.2	Duplex Jumper LC-LC 50/125 μ , OM2, LSZH, armored, grey, 3.0mm, 2m	2.0 m

Technical drawings

OM-Klassifikation ISO/IEC 11801		OM1	OM2	OM3	OM4	OM5
Min. modale Bandbreite mit vollständiger Anregung aller Kernmoden [MHz*km]	850 nm	200	500	1500	3500	4700
	1300 nm	500	500	500	500	2470
Min. modale Bandbreite (effektive) Laser-Bandbreite [MHz*km]	850 nm	n/s	n/s	2000	4700	n/s
	1300 nm	1.5	1.5	1.5	1.5	1,5
Dämpfung [dB/km]	850 nm	3.5	3.5	3.5	3.5	3,5
	1300 nm					

accessory

39962.2	Reel Cleaner(new Version)
39926.1	Miller® Fiber Cleaning Tapes

This datasheet was created automatically on 18-11-2020 . Technical changes reserved.

