

DATASHEET

RJ45 Hirose Connector Set STP, TM31 Cat.6A blue



HRS HIROSE
ELECTRIC
GMBH

Cat.6A

Description

Channel Class EA up to 500 MHz (Cat.6A)
For stranded wires (AWG 24/7, AWG 26/7, AWG 27/7)
Shielded version
Core insulation about 0.9 - 1.0 mm
Cable diameter max. 6.6 mm
The set consists of RJ plug, anti-kink sleeve and guide plate
Suitable crimping tool DCW1002 + DCW1002.1 or 39934.2

General data

Category	6A (TIA)
Model	jack (jack)
Connection type	crimp
Type of connector	RJ45 8(8)
Screened	True
AWG-range for litz wire conductor	24 - 27
Special tool necessary	True
Suitable for round cable	True
Suitable for flat cable	False
Suitable for litz wire conductor	True
Suitable for solid core	False

Available variants

Article no.	Title	Colour
H7642.7-1	RJ45-Hirose Connector TM31 blue, 1 pcs., 3 Elements, Cat. 6a	blue
H7642.7-10	RJ45-Hirose Connector TM31 blue, 10 pcs., 3 Elements, Cat. 6a	blue
H7642.7-50	RJ45-Hirose Connector TM31 blue, 50 pcs., 3 Elements, Cat.6A	blue

This datasheet was created automatically on 18-11-2020 . Technical changes reserved.



DATASHEET



RJ45 Hirose Connector Set STP, TM31 Cat.6A blue

H7642.7-100

RJ45-Hirose Connector TM31 blue ,100 pcs., 3 Elements, Cat.6A

blue

This datasheet was created automatically on 18-11-2020 . Technical changes reserved.



EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

