



2m Mini DisplayPort to DVI Cable, Black

No.: 41952

Connect Mini DisplayPort Devices to a DVI Display

Description

- Connects a Mini DisplayPort equipped device to a DVI display
- Supports resolutions up to 1920x1200@60Hz
- Supports video mirroring and extended desktop modes
- Male to male connections for a secure direct connection
- 2 year warranty

The Lindy Mini DisplayPort to DVI Cable is ideal for connecting a Mini DisplayPort equipped source such as a PC or laptop to a DVI display. It supports high definition video resolutions up to 1920x1200@60Hz.

This cable can also be used to add another display to extend the available desktop workspace and increase productivity, great for use in residential or workplace office setups.

Please note: To use this passive cable, the source device must support dual-mode DisplayPort (also known as DP++).

Technical details

Connectors

- Connector A: Mini DisplayPort Male
- Connector B: DVI-D Male
- Housing Material:
 - Mini DisplayPort: PVC
 - DVI: PVC
- Connector Plating: Gold plated
- Pin Construction: Copper
- Pin Plating: Gold plated
- Dimensions (approx.) WxDxH:
 - Mini DisplayPort: 17.8x10.8x7.9mm [0.7x0.43x0.31in]
 - DVI: 46x39.8x15.9mm [1.81x1.57x0.63in]

Cable Construction

- Length: 2m [6.56ft]
- Standard: DVI-D (Single Link), DisplayPort 1.1
- Colour: Black
- Type: Round
- Jacket Diameter: 4.8mm [0.19in]
- Jacket Material: PVC
- Conductor Material: Tinned Copper
- Conductor Gauge: 30AWG

- Shielding: Aluminum Braid 85%

Specifications

- Supported Bandwidth: 1.65Gbps
- Maximum Resolution: 1920x1200@60Hz
- Nominal Attenuation:
 - 100MHz-450MHz 2.44-5.099dB
 - 450MHz-8100MHz 5.094-32.906dB
- Minimum Bend Radius: 50mm [1.97in]
- Operating Temperature: 0°C - 70°C [32°F - 158°F]
- Storage Temperature: -10°C - 85°C [14°F - 185°F]

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH, UL & California Proposition 65

Purchasing Information

- No.: 41952
- EAN: 4002888419529

This product is also available in other lengths

- 41950 - 0.5m [1.64ft]
- 41951 - 1m [3.28ft]
- 41952 - 2m [6.56ft]
- 41953 - 3m [9.84ft]
- 41954 - 5m [16.44ft]