



20m Cat.6 F/UTP Network Cable, Grey

No.: 44471

RJ45, M/M, 250MHz, Solid, 24AWG

Description

- Twisted Pair Patch Cable with RJ45 connectors
- Cat.6 F/UTP, PVC
- Integrated snagless connector for latch protection
- Gold plated pins for better conductivity and elimination of signal loss
- 10 year warranty

Cat.6 F/UTP PVC network cable with support for bandwidth up to 250MHz and features a snagless design with gold plated contacts for ethernet standards up to 1GBase-T.

Cat.6 cable for operating frequencies up to 250Mhz in a shielded version with foil shielding (F/UTP). Cat.6 cables are widespread throughout the professional sector. They are ideal for Gigabit Ethernet or AV extension applications. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

Available lengths: 10m, 20m, 30m, 40m, 50m, 75m, 100m.

Technical details

Connectors

- Connector A: RJ45 MaleConnector B: RJ45 Male
- Housing Material: Polycarbonate
- Connector Plating: Nickel
- Pin Construction: Copper Alloy
- Pin Plating: Gold plated
- Dimensions (approx.) WxDxH: 11.6x22.8x8.3mm (0.46x0.90x0.33in)

Cable Construction

- Length: 20m (65.62ft)
- Colour: Grey
- Type: Cat.6
- Jacket Diameter: 6.2mm (0.24in)
- Jacket Material: PVC

- Conductor Material: CopperConductor Gauge: 24AWG
- Shielding: Aluminium Foil

Specifications

- Supported Bandwidth: 250MHz
- Nominal Attenuation: 4m 250m: 6db 50db
- Minimum Band Radius: 74mm (2.92in)
 Operating Temperature: -10°C 60°C (14°F 140°F)
 Storage Temperature: -20°C 75°C (-4°F 167°F)

Miscellaneous

- Packaging Type: PolybagWarranty (Years): 10
- Certificated: RoHS, REACH, UL, California Proposition 65

Purchasing Information

- No.: 44471EAN: 4002888444712

This product is also available in other lengths

- 44470 10m (32.81ft)
- 44471 20m (65.62ft)
- 44472 30m (98.43ft)
- 44473 40m (131.23ft)
- 44474 50m (164.04ft)
- 44475 75m (246.06ft)
- 44476 100m (328.08ft)

© LINDY 2021