

USB 3.0 to HDMI Adapter - Slim Design – 1920x1200

**Product ID:** USB32HDES



The USB32HDES Slim USB 3.0 to HDMI Adapter turns a USB 3.0 port into an HDMI output with 1920x1200/1080p video support. The adapter minimizes clutter with a slim design that seamlessly blends with your video cable - an ideal space-saving solution for multi-monitor applications on Ultrabook, laptop, or desktop computers.

Functioning as an external graphics card, this USB to HDMI adapter provides a convenient way to add multi-monitor capability to a USB 3.0-enabled desktop or laptop computer (optimal performance from USB 3.0, backward compatible with USB 2.0).

To save space while travelling, this ultra-portable USB to HDMI adapter features a lightweight, small footprint design that fits easily in a laptop carrying bag.

Leveraging the high-bandwidth (5 Gbps) SuperSpeed USB 3.0 interface, the adapter delivers smooth, high-definition content to your HDMI display/projector. The adapter can be used to mirror your primary desktop, showing the same image on each display, or to extend your desktop to double your workspace and increase your productivity.

The USB32HDES is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Recommended System Requirements:  
CPU: Quad Core 2.4GHz or Higher (i5 recommended)  
RAM: 4GB or higher  
USB 3.0 Port (Backwards compatible with USB 2.0)

## Certifications, Reports and Compatibility

### Applications

- Add a secondary HDMI display with full HD capability
- View large or multiple spreadsheets across several displays

- Use the adapter to connect your PC to your HDMI-equipped projector or display for viewing family pictures and movies
- Add multi-monitor capability to a single computer, to create engaging multimedia presentations
- Great for researchers and writers offering the ability to have reference material on one display and a working document copy on the other
- Run multiple applications on different screens - check your email on one display and search the web on the other

## Features

- Ultra-portable
- SuperSpeed USB 3.0 (5 Gbps)
- Supports High-Definition video resolutions up to 1920x1200/1080p
- USB-powered - No external power adapter required
- Supports Mirrored, Extended or Primary display configurations
- Supports display rotation
- Slim lightweight design

---

### Hardware

Warranty	2 Years
AV Input	USB 3.0
AV Output	HDMI
Audio	Yes
USB Pass-Through	No
Memory	16MB
Chipset ID	Trigger - T5-302

---

### Performance

Maximum Digital Resolutions	1920x1200/1080p
Supported Resolutions	Widescreen(16/32 bit): 1920x1200, 1920x1080, 1680x1050, 1600x900, 1440x900, 1360x768, 1280x800, 1280x768, 1280x720



Standard(16/32 bit):

1600x1200, 1400x1050, 1280x1024, 1280x960, 1152x864, 1024x768, 800x600

Wide Screen Supported Yes

Audio Specifications 2-Channel Stereo (48Khz)

General Specifications This USB video adapter uses a Trigger family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, please avoid using devices with a DisplayLink or Fresco family chipset.

#### Connector(s)

Connector A USB Type-A (9 pin) USB 3.0 (5 Gbps)

Connector B HDMI (19 pin)

#### Software

OS Compatibility Windows 10 (32/64)  
Windows 8 / 8.1 (32/64)  
Windows 7(32/64)  
Windows Vista (32/64)  
Windows XP (32/64)

Microsoft WHQL Certified Yes

#### Special Notes / Requirements


System and Cable Requirements System Processor: Quad Core 2.4GHz (i5 recommended)  
System Memory: 4GB

Note This USB video adapter uses a Trigger family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, avoid using devices with different family chipsets, such as DisplayLink or Fresco Logic

Connect a maximum of five USB video adapters on a single computer. Support for multiple adapters will vary depending upon your system resources

This USB video adapter is not intended for graphical intensive applications, such as gaming

#### Power



Power Source                      USB-Powered

**Environmental**

Operating Temperature      0C to 50C (32F to 122F)

Storage Temperature        -10C to 75C (14F to 167F)

Humidity                         < 85% non-condensing

**Physical Characteristics**

Color                                Black

Material                            Plastic

Cable Length                    2.4 in [62 mm]

Product Length                7.5 in [19 cm]

Product Width                 1.0 in [25 mm]

Product Height                0.5 in [12 mm]

Weight of Product            0.9 oz [25 g]

**Packaging Information**

Package Length                6.9 in [17.5 cm]

Package Width                 5.8 in [14.8 cm]

Package Height                1.3 in [32 mm]

Shipping (Package) Weight   5.1 oz [144 g]

**What's in the Box**

Included in Package        Slim USB 3.0 Video Adapter

   Driver CD

   instruction manual

*\*Product appearance and specifications are subject to change without notice.*

