

1 m (3.3 ft.) USB-C to Mini DisplayPort Cable - 4K 60Hz - Black

Product ID: CDP2MDPMM1MB



This USB-C to Mini DisplayPort cable lets you connect your Thunderbolt 3 or USB Type-C enabled device to a Mini DP monitor with just one cable, for a convenient, clutter-free connection.

Astonishing Picture Quality

Harness the video capabilities that are built into your USB-C connection. The USB Type-C to Mini DisplayPort cable delivers the astonishing quality of Ultra HD to your 4K display, at resolutions up to 3840×2160 . Plus, the adapter is backward compatible with 1080p displays, which makes it a great accessory for home, office or other work environments.





Clutter-Free Installation

At 1 m (3.3 ft.) in length, this Mini DP cable delivers a compact connection that eliminates excess adapters and cabling, ensuring a tidy, professional installation. For longer installations, we also offer a 6 ft. (1.8 m) USB-C to mDP cable, enabling you to choose the right cable length for your custom installation needs.

Hassle-Free Setup

For easy operation and installation, this USB 3.1 Type-C to Mini DP adapter cable supports plug-and-play installation on both Windows and Mac computers.

CDP2MDPMM1MB is backed by a 3-year StarTech.com warranty and free lifetime technical support.





Certifications, Reports and Compatibility











Applications

- Connect your MacBook or USB-C device to an mDP monitor
- Ideal for home office or hot desk environments
- Experience crisp visuals with support for 4K 60Hz
- Deliver enriched presentations on the go

Features

- Reduce clutter with a USB-C to mDP adapter and cable in one
- Get astonishing picture quality with support for UHD video resolutions up to 4K 60Hz
- Make the perfect connection with a Mini DisplayPort cable that works with any USB Type-C enabled device
- Hassle-free connectivity with the reversible USB-C connector
- Compatible with Thunderbolt 3 and USB 3.1 Type-C ports that support DP Alt Mode



Data Sheet

| | Warranty | 3 Years |
|---------------------------------|-----------------------------|--|
| Hardware | Adapter Style | Cable Adapters |
| | AV Input | USB Type-C |
| | AV Output | Mini-DisplayPort |
| | Chipset ID | STMicroelectronics - STM32F072CBU6 |
| | Ports | 1 |
| Performance | Audio Specifications | 7.1 surround sound |
| | Maximum Digital Resolutions | 3840x2160 @ 60 Hz |
| | Supported Resolutions | 1024x768 1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1200 2560x1440 2560x1600 3840x2160 (Ultra HD 4K) |
| | Wide Screen Supported | Yes |
| Connector(s) | Connector A | 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input |
| | Connector B | 1 - Mini-DisplayPort (20 pin) Male Output |
| Special Notes / Requirements | Note | Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. |
| Environmental | Humidity | 25%-60%RH |
| | Operating Temperature | 5°C to 35°C (41°F to 95°F) |
| | Storage Temperature | -20°C to 60°C (-4°F to 140°F) |
| Physical Characteristics | Cable Length | 3.3 ft [1 m] |
| | Color | Black |
| | Product Height | 0.4 in [1 cm] |
| | Product Length | 3.3 ft [1 m] |
| | Product Width | 0.8 in [20 mm] |
| | Weight of Product | 0.9 oz [25 g] |
| Packaging Information | Package Height | 0.5 in [12 mm] |
| | Package Length | 8.7 in [22 cm] |
| | Package Width | 7.9 in [20 cm] |
| | Shipping (Package) Weight | 0.1 lb [0 kg] |
| | | |

Product appearance and specifications are subject to change without notice.