



# 1m USB 2.0 Type A Extension Cable, Anthra Line, Grev

# No.: 36712

USB Type A Male to A Female

# Description

- Professional choice USB 2.0 Type A Extension, grey, cable for commercial and high performance AV and IT installations
- Supports data transfer speeds up to 480Mbps
- Robust PVC housing, nickel connectors and gold plated contacts
- Double shielded cable with grey finish, corrosion resistant tinned copper conductors
- USB 2.0, 480Mbps; 10 year warranty

From the Lines cable connectivity concept developed by Lindy, Anthra Line USB 2.0 Type A Extension, grey, cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line USB 2.0 cables are premium connections that feature double shielded construction with copper conductors for performance and corrosion resistance. High quality gold plated contacts and nickel connectors maintain optimal signal integrity and maximum reliability.

Data transfer speeds up to 480Mbps are supported for the quick and effortless transfer of large data volumes.

This product features a grey finish effect on the cable.

Anthra Line USB 2.0 Type A Extension, Grey, cables are available in lengths from 0.2m, 0.5m, 1m, 2m, 3m and 5m

## **Technical details**

#### Connectors

- Connector A: USB 2.0 Type A Male
- Connector B: USB 2.0 Type A Female
- Housing Material: PVC
- Connector Plating: Nickel
  Pin Construction: Copper
- Pin Construction.
   Pin Plating: Gold
- Pin Plating. Gold
  Dimensions (approx.) WxDxH:
  - A (M): 15.5x35x7.8mm (0.61x1.38x0.31in)
    - A (F): 17x35x9.8mm (0.67x1.38x0.39in)

#### **Cable Construction**

• Length: 1m (3.28ft)

- Standard: USB 2.0
- Colour: Grey .
- Type: Round
- Jacket Diameter: 4.4mm (0.17in)
  Jacket Material: PVC
- Conductor Material: Tinned Copper
   Conductor Gauge: 26/28AWG
- Shielding: Aluminium Magnesium Braid

#### Specifications

- Supported Bandwidth: 480Mbps
- Maximum Resolution: -
- Nominal Attenuation: 5.8db/km
  Minimum Band Radius: 16mm (0.63in)
- Operating Temperature: 0°C 60°C (32°F 140°F)
   Storage Temperature: 0°C 60°C (32°F 140°F)
- ATC Approved: -

### Miscellaneous

- Packaging Type: Polybag
  Warranty (Years): 10
- Certificated: RoHS, REACH & UL

#### **Purchasing Information**

- No.: 36712
- EAN: 4002888367127

This product is also available in other lengths

- 36710 0.2m (0.66ft)
  36711 0.5m (1.64ft)
  36712 1m (3.28ft)
  36713 2m (6.56ft)
  36714 3m (9.84ft)
  36715 5m (16.44ft)

© LINDY 2021