






MAX430S - HDS

 464 x 366 x H176 mm
18.27 x 14.41 x H6.93 inch.

 426 x 290 x H159 mm
16.77 x 11.42 x H6.26 inch.

 45 + 114 mm
1.77 + 4.49 inch.

 VERSION S: 3,04 kg / 6.70 lb
VERSION HDS: 3,52 kg / 7.76 lb




HIGH DENSITY
CUBED FOAM
VIDEO




- **WATERTIGHT SEAL AROUND LID / GUARNIZIONE ERMETICA**
- **AUTOMATIC PRESSURE RELEASE VALVE / VALVOLA AUTOMATICA DI PRESSURIZZAZIONE**
- **EASY TO OPEN DOUBLE THROW LATCHES / CHIUSURE DI SICUREZZA A DOPPIO STEP**
- **LOAD TESTED SOFT GRIP HANDLE / MANICO MORBIDO AD ALTA ERGONOMICITÀ**
- **STACKABLE INTERLOCKING SYSTEM / SISTEMA DI IMPILABILITÀ**
- **THICK BODY MATERIAL / PARETI SPESSE ANTIURTO**
- **EXTRA FIXING POINTS / PUNTI DI FISSAGGIO PER VARIE APPLICAZIONI**
- **FULLY LENGTH HINGES / CERNIERA LUNGO TUTTO IL PROFILO DELLA VALIGIA**
- **NYLON PINS, CORROSION FREE / PERNI IN NYLON ANTI CORROSIONE**
- **SCREEN PRINTING AND RESIN LABEL SPACE / SERIGRAFIA ED ETICHETTA RESINATA**
- **MATERIAL: POLYPROPYLENE COPOLYMER / MATERIALE: POLIPROPILENE COPOLIMERO**
- **LATCHES: NYLON / SERRATURE IN NYLON**
- **O-RING: POLYMER / GUARNIZIONE POLIMERO**

- **INTERNAL CUBIC VOLUME: 19642860 CUBIC MM - 0.6936 CUBIC FEET / VOLUME: 19642860 MM CUBI**
- **VOLUME CAPACITY: 19.64 LT / CAPACITÀ: 19.64 LT**
- **PCS PER CARTON: 2 / PEZZI PER CARTONE: 2**
- **WEIGHT OF THE FULL CARTON: 6.95 KG - 15.32 LBS. / PESO DEL CARTONE: 6.95 KG**
- **MOULDING: INJECTION MOLDED / STAMPAGGIO: AD INIEZIONE**
- **RANGE TEMPERATURE: -30 / 90°C (-22 / 194°F) / RANGE DI TEMPERATURA: -30 / 90°C (-22 / 194°F)**
- **ACCESSORIES: CUBED & CONVOLUTED FOAMS - PADDED DIVIDERS - LID ORGANIZER - SHOULDER STRAP / SPUGNE CUBETTATE & SPUGNE BUGNATE - DIVISORIE IMBOTTITE - TASCA ORGANIZER - TRACCOLLA IMBOTTITA**

IP67 RATING **ATA 300** **MIL SPECS** DEF STAN 81-41
STANAG 4280



+



+



=



Base foam

1 x 20 mm / 1 x 0.79 inch

Cubed foam

2 x 40 mm / 2 x 1.57 inch


Convuluted foam

1 x 45 mm / 1 x 1.77 inch


MAX430S



+



+



=



Base foam

1 x 20 mm / 1 x 0.79 inch

High Density Cubed foam

2 x 40 mm / 2 x 1.57 inch

Convuluted foam

1 x 45 mm / 1 x 1.77 inch

MAX430HDS