



MAX820S

 880 x 660 x H483 mm
34.64 x 25.98 x H19.01 inch.

 820 x 600 x H450 mm
32.28 x 23.62 x H17.71 inch.

 70 + 380 mm
2.75 + 14.96 inch.

 21 kg / 46.29 lb



SIDE HANDLES
+ **LARGE FOLD DOWN HANDLE**
MANIGLIA LATERALE
SU ENTRAMBI I LATI
+ MANIGLIONE PER TRASPORTO



- **WATERTIGHT SEAL AROUND LID** / GUARNIZIONE ERMETICA
- **AUTOMATIC PRESSURE RELEASE VALVE** / VALVOLA AUTOMATICA DI PRESSURIZZAZIONE
- **EASY TO OPEN DOUBLE THROW LATCHES** / CHIUSURE DI SICUREZZA A DOPPIO STEP
- **LOAD TESTED SOFT GRIP HANDLE** / MANICO MORBIDO AD ALTA ERGONOMICITÀ
- **STACKABLE INTERLOCKING SYSTEM** / SISTEMA DI IMPILABILITÀ
- **THICK BODY MATERIAL** / PARETI SPESSE ANTIURTO
- **FULLY LENGTH HINGES** / CERNIERA LUNGO TUTTO IL PROFILO DELLA VALIGIA
- **NYLON PINS, CORROSION FREE** / PERNI IN NYLON ANTI CORROSIONE
- **SCREEN PRINTING AND RESIN LABEL SPACE** / SERIGRAFIA ED ETICHETTA RESINATA
- **MATERIAL: POLYPROPYLENE COPOLYMER** / MATERIALE: POLIPROPILENE COPOLIMERO
- **LATCHES: NYLON** / SERRATURE IN NYLON
- **O-RING: POLYMER** / GUARNIZIONE POLIMERO
- **WHEELS WITH STAINLESS STEEL PIN** / RUOTE CON ASSALE IN ACCIAIO INOX


- **INTERNAL CUBIC VOLUME: 221400000 CUBIC MM - 7.818 CUBIC FEET** / VOLUME: 221400000 MM CUBI
- **VOLUME CAPACITY: 221.4 LT** / CAPACITÀ: 221.4 LT
- **PCS PER CARTON: 1** / PEZZI PER CARTONE: 1
- **WEIGHT OF THE FULL CARTON: 24 KG - 52.91 LBS.** / PESO DEL CARTONE: 24 KG
- **MOULDING: INJECTION MOLDED** / STAMPAGGIO: AD INIEZIONE
- **RANGE TEMPERATURE: -30 / 90°C (-22 / 194°F)** / RANGE DI TEMPERATURA: -30 / 90°C (-22 / 194°F)
- **ACCESSORIES: CUBED & CONVOLUTED FOAMS** / SPUGNE CUBETTATE & SPUGNE BUGNATE

IP67 RATING


ATA 300

MIL SPECS

DEF STAN 81-41
STANAG 4280



+



+



=



Base foam

1 x 45 mm / 1 x 1.97 inch

Cubed foam

4 x 65 mm + 1 x 70 mm /
4 x 2.56 inch + 1 x 2.75 inch


Convuluted foam

1 x 65 mm / 1 x 2.56 inch


MAX820S



+



+



=



Base foam

1 x 45 mm / 1 x 1.97 inch

High Density Cubed foam

4 x 65 mm + 1 x 70 mm /
4 x 2.56 inch + 1 x 2.75 inch

Convuluted foam

1 x 65 mm / 1 x 2.56 inch

MAX820HDS