



## DisplayPort 1.2 to HDMI, DVI & VGA Active Converter

No.: 41028

Connects a DisplayPort source to an HDMI, DVI or VGA display

### Description

- Converts a DisplayPort signal to HDMI, DVI or VGA
- Supports HDMI resolutions up to 4K@30Hz, VGA up to Full HD and DVI up to and above Full HD
- Easily connect with a single legacy or modern display at any one time
- Compact, portable design
- 2 year warranty

The Lindy DisplayPort to HDMI, DVI and VGA Converter allows users to connect either a HDMI, DVI or VGA screen to a Displayport source. Supporting 4K resolutions up to 3840x2160@30Hz on HDMI displays, content can be viewed with superior clarity and stunning accuracy. DVI monitors are supported with a maximum resolution of 1920x1200@60Hz, VGA monitors and projectors up to 1920x1080@60Hz.

With its lightweight, low profile design, this converter easily fits into a notebook bag and simply expands available connectivity options, so users can connect to the most commonly used digital and analogue video equipment, without having to carry multiple adapters - ideal for BYOD applications.

### Technical details

#### Specifications

- AV Interface: DisplayPort to HDMI, VGA, DVI
- Interface Standard: DisplayPort 1.2, HDMI 1.4, VGA, DVI-D
- Supported Bandwidth: 21.6Gbps
- Maximum Input Resolution: 3840x2160@30Hz
- Maximum Output Resolution:
  - VGA: 1920x1200@60Hz
  - HDMI: 3840x2160@30Hz
  - DVI: 1920x1200@60Hz
- Chipset: Paradedtech PS8339
- HDCP Support: HDCP 1.4
- Supported Audio: Pass-through for HDMI
- Separate Audio Ports: -
- Special Features: -

#### Connectors

- Input: DisplayPort Male
- Output:
  - HDMI Type A Female

- VGA Female
- DVI-D Female

#### Physical properties

- Dimensions (approx.) WxDxH:
  - 60x60x16.4mm [2.36x2.36x0.65in] / Housing
  - 20x44.5x11mm [0.79x1.75x0.43in]
- Cable Length: 200mm [7.87in]
- Housing Material: ABS
- Jacket Material: PVC
- Jacket Diameter: 6mm [0.24in]
- Minimum Bend Radius: 60mm [2.36in]
- Net Weight: 0.053kg [0.12lb]
- Operating Temperature: 0°C - 70°C [32°F - 158°F]
- Storage Temperature: -20°C - 70°C [-4°F - 158°F]
- Humidity: 10 - 85% RH (non-condensing)
- Colour: White

#### Miscellaneous

- Packaging Type: Polybag
- Packaging Dimensions: 160x160x20mm [6.3x6.3x0.79in]
- Gross Weight: 0.076kg [0.17lb]
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

#### Package Contents

- DisplayPort 1.2 to HDMI 1.4, DVI & VGA Active Converter

#### Purchasing Information

- No.: 41028
- EAN: 4002888410281