



USB Type C to Multi-AV Converter

No.: 43279

Connect a DisplayPort, HDMI, DVI or VGA display to a single USB Type C port

Description

- Allows users to connect a DisplayPort, HDMI, DVI or VGA device to a USB Type C port
- Supports HDMI and DP resolutions up to 4K@60Hz, VGA and DVI up to 1920x1200@60Hz
- Requires DisplayPort Alternate support from the USB Port/Bus
- Easily connect a single legacy or modern display at any one time
- 2 year warranty

USB Type C to Multi-AV converters allow users to connect multiple AV interfaces to a USB C equipped device. The Lindy USB Type C to Multi-AV Converter connects either an HDMI, DisplayPort, DVI or VGA display to a Macbook, Ultrabook or Notebook with USB DisplayPort Alternate Mode.

Supporting full 4K Ultra HD resolutions up to 3840x2160@60Hz on DP and HDMI displays, content can be viewed with superior clarity and stunning accuracy. DVI and VGA monitors are supported with a maximum resolution of 1920x1200@60Hz.

With its lightweight, low profile design, this converter easily fits into a notebook bag and simply expands available connectivity options, so users can connect to the most commonly used digital and analogue video equipment, without having to carry multiple adapters - ideal for BYOD applications. The converter is powered by the USB Bus, therefore no external power supply is necessary. Installation is simple as no drivers are required and Type-C's reversible design has been developed to work regardless of which way the cable is inserted into the port.

Technical details

Specifications

- AV Interface: USB to DP / HDMI / DVI / VGA
- Interface Standard: DisplayPort 1.2, HDMI 2.0, DVI, VGA
- Supported Bandwidth: 21.6Gbps
- Maximum Input Resolution: 4K 60Hz
- Maximum Output Resolution: 3840x2160@60Hz RGB 8bit (DP), 3840x2160@60Hz RGB 8bit (HDMI), 1920x1200@60Hz (DVI) & 1920x1200@60Hz (VGA)
- Chipset: VL103, PS176, PS8348B, AG6320
- Compatibility: USB Type C or Thunderbolt 3 equipped computers with DisplayPort Alternate Mode support (incl. Apple M1)
- Power Delivery: -
- HDCP Support: HDCP 2.2
- Supported Audio: Audio for DP and HDMI
- Separate Audio Ports: -
- Special Features: -

Connectors

- Inputs: USB Type C (Male)
- Outputs: HDMI Type A (Female), DisplayPort (Female), DVI-I (Female), VGA (Female)
- Power: Bus-powered

Physical Properties

- Dimensions (approx.) WxDxH:
 - Connector: 21x13x7mm (0.83x0.51x0.28in)
 - Housing: 105.5x46x14.5mm (4.15x1.81x0.57in)
- (Fixed) Cable Length: 145mm (5.71in)
- Housing Material: Plastic
- Net Weight: 0.077kg (0.17lb)
- Operating Temperature: 0° to 40° (32°F - 104°F)
- Storage Temperature: -10° to +70° (14°F - 158°F)
- Humidity: 10 - 85% RH (non-condensing)
- Power Requirements: -
- Colour: White

Miscellaneous

- Packaging Type: Polybag
- Packaging Dimensions: 174x15x194mm (6.85x0.59x7.64in)
- Gross Weight: 0.086kg (0.19lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH, Calif. Prop. 65

Package Contents

- USB Type C to Multi-AV Active Converter

Purchasing information

- No.: 43279
- EAN: 4002888432795