


Patch & Instrument Cable SC-Onyx 2025 MKII; 2 x 1 x 0,25 mm²; PVC; 8,3 x 3,8 mm; black Art. No.: 320-0101

ANALOG

OFC



General Data

Article number :	320-0101
Name :	SC-Onyx 2025 MKII
EAN :	4049371003292
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Studio / Broadcast
Application area :	Installation
Application :	Patch & Instrument Cable
Colour :	black
BPVo-Euroclass :	Fca

Technical Data

Signal transmission :	asymmetrical
Construction :	LI2YDY2x0,25mm ²
Jacket material :	PVC
Number of Channels (audio) :	2
Inner conductor (audio) :	1
Inner conductor (audio) [mm ²] :	0,25
Inner conductor Ø (audio) [mm] :	0,56
AWG (audio) :	24
Shielding :	Copper spiral shielding
Shielding factor [%] :	90
Copper strands (audio) :	32
Copper strand Ø (audio) [mm] :	0,10
Conductor insulation material :	PE
Weight per 1 m [g] :	38
UV-resistant :	yes
Fire load per m [kWh] :	0,23
Style variant :	round
Packing :	100 m spool
Temperature min. [°C] :	-20
Temperature max. [°C] :	70
Width [mm] :	8,3
Height [mm] :	3,8

Electrical Data

Capac. cond./shield. per 1 m (audio) [pF] :	120
Insulation resist. per 1 km [GΩ] :	1
Insulation resist. per 1 km (audio) [GΩ] :	1
Conductor resistance per 1 km [Ω] :	115