

# DATASHEET

## Duplex Jumper LC-ST 50/125 $\mu$ , OM2



### Description

Fiber jumper are well defined components in international standard of structured cabling ISO/IEC11801. Due to many different network protocols created in the last 25 years , also a wide range of connectors had been developed. Some of them are still important today: LC, SC, E2000®, MPO/MTP.

Fiber jumper(patchcord) are defined as shortest connection between passive interface and active deviceport, regarding structured cabling standard. Rating of performance, known as category, as well as performance of total transmission channel, known as link class, Similar descriptions for patchcords: Connection cable, drop cable, adapter cable, interconnecting cord, Jumper

### General data

Fibre type	Multimode 50/125
Category	OM2
Bend optimized fiber	OM2 acc. to IEC60793-2-10 type A1a.1
Number of fibres	2
Anti-kink sleeve	put-on
Type of connector connection 1	LC-Duplex
Connector colour 1	beige
Type of connector connection 2	ST

### Mechanical characteristics

Max. Tension	160 N
Min. Bending radius (Static)	10xOD
Min. Bending radius (Dynamic)	20xOD

### Cable construction

Cable type	I-V(ZN) H
Cable Construction	Duplex
Cable Ø	2.0 mm

This datasheet was created automatically on 18-11-2020 . Technical changes reserved.



# DATASHEET

## Duplex Jumper LC-ST 50/125 $\mu$ , OM2

### Cable sheath

Colour outer sheath	orange
Jacket Material	LSZH
Flame retardant	According to EN 50265-2-1
Halogen free	acc. IEC60754-1
Low smoke	acc. IEC61034-1

### Environmental conditions

Operating Temperature	-20 – 75 °C
Storage Temperature	-20 – 85 °C

### Transmission characteristics

Quality class multimode	A/1 according to IEC-61753-222-2
-------------------------	----------------------------------

### Standards, approvals, certifications

Cable Conform to Standard	IEC 60793-2
---------------------------	-------------

### Available variants

Article no.	Title	Length
O0321.0,5	Duplex Jumper LC-ST 50/125 $\mu$ , OM2, LSZH, orange, 2.0mm 0.5m	0.5 m
O0321.1	Duplex Jumper LC-ST 50/125 $\mu$ , OM2, LSZH, orange, 2.0mm 1m	1.0 m
O0321.1,5	Duplex Jumper LC-ST 50/125 $\mu$ , OM2, LSZH, orange, 2.0mm 1.5m	1.5 m
O0321.2	Duplex Jumper LC-ST 50/125 $\mu$ , OM2, LSZH, orange, 2.0mm 2m	2.0 m
O0321.2,5	Duplex Jumper LC-ST 50/125 $\mu$ , OM2, LSZH, orange, 2.0mm 2.5m	2.5 m
O0321.3	Duplex Jumper LC-ST 50/125 $\mu$ , OM2, LSZH, orange, 2.0mm 3m	3.0 m
O0321.4	Duplex Jumper LC-ST 50/125 $\mu$ , OM2, LSZH, orange, 2.0mm 4m	4.0 m
O0321.5	Duplex Jumper LC-ST 50/125 $\mu$ , OM2, LSZH, orange, 2.0mm 5m	5.0 m
O0321.7,5	Duplex Jumper LC-ST 50/125 $\mu$ , OM2, LSZH, orange, 2.0mm 7.5m	7.5 m
O0321.10	Duplex Jumper LC-ST 50/125 $\mu$ , OM2, LSZH, orange, 2.0mm 10m	10.0 m
O0321.15	Duplex Jumper LC-ST 50/125 $\mu$ , OM2, LSZH, orange, 2.0mm 15m	15.0 m
O0321.20	Duplex Jumper LC-ST 50/125 $\mu$ , OM2, LSZH, orange, 2.0mm 20m	20.0 m
O0321.25	Duplex Jumper LC-ST 50/125 $\mu$ , OM2, LSZH, orange, 2.0mm 25m	25.0 m
O0321.30	Duplex Jumper LC-ST 50/125 $\mu$ , OM2, LSZH, orange, 2.0mm 30m	30.0 m
O0321.35	Duplex Jumper LC-ST 50/125 $\mu$ , OM2, LSZH, orange, 2.0mm 35m	35.0 m
O0321.40	Duplex Jumper LC-ST 50/125 $\mu$ , OM2, LSZH, orange, 2.0mm 40m	40.0 m
O0321.45	Duplex Jumper LC-ST 50/125 $\mu$ , OM2, LSZH, orange, 2.0mm 45m	45.0 m
O0321.50	Duplex Jumper LC-ST 50/125 $\mu$ , OM2, LSZH, orange, 2.0mm 50m	50.0 m


This datasheet was created automatically on 18-11-2020 . Technical changes reserved.



# DATASHEET

## Duplex Jumper LC-ST 50/125 $\mu$ , OM2

### Technical drawings



OM-Klassifikation ISO/IEC 11801		OM1	OM2	OM3	OM4	OM5
Min. modale Bandbreite mit vollständiger Anregung aller Kernmoden [MHz*km]	850 nm	200	500	1500	3500	4700
	1300 nm	500	500	500	500	2470
Min. modale Bandbreite (effektive) Laser-Bandbreite [MHz*km]	850 nm	n/s	n/s	2000	4700	n/s
	1300 nm	1.5	1.5	1.5	1.5	1,5
Dämpfung [dB/km]	850 nm	3.5	3.5	3.5	3.5	3,5
	1300 nm					

### accessory

39962.2	Reel Cleaner(new Version)
39926.1	Miller® Fiber Cleaning Tapes

This datasheet was created automatically on 18-11-2020 . Technical changes reserved.