



## NO24FDW-A

The rear compatibility of opticalCON MTP® 24 chassis fitting with standard MTP® 24 (ELITE male with 20 N springforce) breakout cable allows easy adaptation to fiber standard connectors such as LC, SC, ST. The approved dust shutter ensures high mating cycles and minimal maintenance.

### Features & Benefits

- Ruggedized and dirt-protected 24-channel fiber optic connection system
- Laser protective metal shutter seals dust proof with two-component rubber gasket
- Accommodates standard MTP® ELITE MALE with 20 N springforce connectors on the rear for simple installation
- For point-to-point multichannel routing
- IP65 ingress protection in mated condition with SCDP-\*

## Technical Information

Product	
<b>Title</b>	NO24FDW-A
<b>Gender</b>	female

Mechanical	
<b>Insertion force</b>	< 45 N
<b>Withdrawal force</b>	< 45 N
<b>Lifetime</b>	> 2'500 mating cycles
<b>Locking force</b>	1'000 N
<b>Wiresize</b>	
<b>Locking device</b>	Push-Pull
<b>Mounting direction</b>	Front mounting
<b>Chassis shape</b>	D

Environmental	
<b>Flammability</b>	UL 94 V-0
<b>Temperature range</b>	-40 °C to +75 °C

Optical	
<b>Insertion loss</b>	< 0.9 dB / connection